

# TORQUE TOOL SPECIALIST



## POWER PACKS

*BOLTING PROBLEM SOLVERS SINCE 2004*

TEL : 1-484-951-6628

SALES : [BOLTING@NIBTORQUE.COM](mailto:BOLTING@NIBTORQUE.COM)

FAX : 1-866-780-9316

WEB : [WWW.NIBTORQUE.COM](http://WWW.NIBTORQUE.COM)

# HYDRAULIC TORQUE WRENCH POWER PACKS

*ELECTRIC POWERED*

*WITH FAN COOLED OIL COOLER/HEAT EXCHANGER*



	Performance	Oil Flow	Dimensions	Weight	Reservoir	Power
<b>WINDMASTER</b>	0-1100 psi 1100-3200 psi 3200-10000 psi	390 cu. in/min 110 cu. in/min 43 cu. in/min	Length: 16.2 in Width: 11.8 in Height: 17.5 in	59 lbs	2 Gal.	.75 hp
Part Number <b>WINDMASTER</b>	0-76 bar 76-220 bar 220-700 bar	6.4 Liter/min 1.8 Liter/min 0.7 Liter/min	Length: 41 cm Width: 30 cm Height: 44 cm	27 kg	7.57 L.	.56 kw



	Performance	Oil Flow	Dimensions	Weight	Reservoir	Power
<b>EXPRESS MAX</b>	0-1100 psi 1100-3200 psi 3200-10000 psi	390 cu. in/min 110 cu. in/min 43 cu. in/min	Length: 16.2 in Width: 11.8 in Height: 17.5 in	59 lbs	2 Gal.	.75 hp
Part Number <b>EXE-MAX</b>	0-76 bar 76-220 bar 220-700 bar	6.4 Liter/min 1.8 Liter/min 0.7 Liter/min	Length: 41 cm Width: 30 cm Height: 44 cm	27 kg	7.57 L.	.56 kw



Model Number	Maximum Oil Flow vs Pressure	Length	Width	Height	Weight
<b>E115-FC</b> Single Port	720 cu. in./min @ 100 psi (11.8 L/min @ 7 bar)  56 cu. in./min @ 10000 psi (.91 L/min @ 700 bar)	9.5" 241mm	17.1" 434mm	8.1" 460mm	46 lb 20.8kg
<b>E115-4FC</b> 4 Port	720 cu. in./min @ 100 psi (11.8 L/min @ 7 bar)  56 cu. in./min @ 10000 psi (.91 L/min @ 700 bar)	9.5" 241mm	17.1" 434mm	8.1" 460mm	46 lb 20.8kg

Power Requirements: 115V-60HZ / 28 amp • Flow: 720 cu in / 11.8 lpm per min • 1 1/8 HP motor (.9Kw)

*WITHOUT FAN COOLED OIL COOLER/HEAT EXCHANGER*



Model Number	Maximum Oil Flow vs Pressure	Length	Width	Height	Weight
<b>E115</b> Single Port	720 cu. in./min @ 100 psi (11.8 L/min @ 7 bar)  56 cu. in./min @ 10000 psi (.91 L/min @ 700 bar)	9.5" 241mm	17.1" 434mm	8.1" 460mm	46 lb 20.8kg
<b>E115-4</b> 4 Port	720 cu. in./min @ 100 psi (11.8 L/min @ 7 bar)  56 cu. in./min @ 10000 psi (.91 L/min @ 700 bar)	9.5" 241mm	17.1" 434mm	8.1" 460mm	46 lb 20.8kg

Power Requirements: 115V-60HZ / 25 amp • Flow: 720 cu in / 11.8 lpm per min • 1 1/8 HP motor (.9Kw)

*ULTRA LIGHT ULTRA PORTABLE POWER PACKS*



	Performance	Oil Flow	Dimensions	Weight	Reservoir	Power
<b>EXPRESS MINI</b>	0-1100 psi 1100-3200 psi 3200-10000 psi	235 cu. in/min 66 cu. in/min 25cu. in/min	Length: 12.6 in Width: 8.7 in Height: 17.0 in	31 lbs	1 Gal.	.35 hp
Part Number <b>EXE-MINI</b>	0-76 bar 76-220 bar 220-700 bar	3.9 Liter/min 1.1 Liter/min 0.4 Liter/min	Length: 32 cm Width: 22 cm Height: 43 cm	14 kg	3.78 L.	.26 kw

# HYDRAULIC TORQUE WRENCH POWER PACKS

PNEUMATIC POWERED



<b>EXPRESS Max Air</b>	0-1100 psi 1100-3200 psi 3200-10000 psi	460 cu. in./min 153 cu. in./min 55 cu. in./min	Length: 20.5 in Width: 13.8 in Height: 20 in	66 lbs	2 Gal.	3.75 hp
<b>Part Number EXA-MAX</b>	0-76 bar 76-220 bar 220-700 bar	7.5 liter/min 2.5 liter/min 0.9 liter/min	Length: 52 cm Width: 35 cm Height: 51 cm	30 kg	7.57 L.	2.80 kw



<b>EXPRESS Mini Air</b>	0-1100 psi 1100-3200 psi 3200-10000 psi	275 cu. in./min 86 cu. in./min 32 cu. in./min	Length: 12.2 in Width: 11.5 in Height: 16.5 in	41 lbs	1 Gal.	1.50 hp
<b>Part Number EXA-MINI</b>	0-76 bar 76-220 bar 220-700 bar	4.5 liter/min 1.4 liter/min 0.5 liter/min	Length: 31 cm Width: 29 cm Height: 42 cm	19 kg	3.78 L.	1.12 kw

Power Requirements: 70-100psi / 50 cfm air • Flow: 670 cu in / 11.1 lpm per min. • Powerful 3 HP motor (2.24Kw)



Model Number	Maximum Oil Flow vs Pressure	Length	Width	Height	Weight
<i>Model P+ Single Port</i>	670 cu. in./min @ 100 psi (11.1 liter/min @ 7 bar)  55 cu. in./min @ 10000 psi (1 liter/min @ 700 bar)	9.5" 241mm	16.5" 419mm	19.8" 503mm	58 lb 26kg
<i>Model P+4 Four Port</i>	670 cu. in./min @ 100 psi (11.1 liter/min @ 7 bar)  55 cu. in./min @ 10000 psi (1 liter/min @ 700 bar)	9.5" 241mm	16.5" 419mm	19.8" 503mm	58 lb 26kg

Power Requirements: 70-100psi / 95 cfm air • Flow: 1340 cu. in. / 22 lpm per min



Model Number	Maximum Oil Flow vs Pressure	Length	Width	Height	Weight
<i>Model P+ TWIN Single Port</i>	1340 cu. in./min @ 100 psi (22 liter/min @ 7 bar)  110 cu. in./min @ 10000 psi (2 liter/min @ 700 bar)	19" 282mm	16.5" 840mm	19.8" 503mm	116 lb 52kg
<i>Model P+4 TWIN Four Port</i>	1340 cu. in./min @ 100 psi (22 liter/min @ 7 bar)  110 cu. in./min @ 10000 psi (2 liter/min @ 700 bar)	19" 282mm	16.5" 840mm	19.8" 503mm	116 lb 52kg

## ELECTRIC POWER PACKS CONT.

Power Requirements: 220v-50hz / 26 amp • Flow: 1440 cu. in. / 23.6 lpm per min



Model Number	Maximum Oil Flow vs Pressure	Length	Width	Height	Weight
<i>E230 Twin 230V Single Port</i>	1440 cu. in./min @ 100 psi (23.6 liter/min @ 7 bar)  112 cu. in./min @ 10000 psi (2 liter/min @ 700 bar)	19" 282mm	16.5" 840mm	19.8" 503mm	116 lb 52kg
<i>E230 Twin-4 230V 4 Port</i>	1440 cu. in./min @ 100 psi (23.6 liter/min @ 7 bar)  112 cu. in./min @ 10000 psi (2 liter/min @ 700 bar)	19" 282mm	16.5" 840mm	19.8" 503mm	116 lb 52kg